


FULLY INSULATED FEMALE QUICK DISCONNECTS

PVC母全绝缘端头

- Material
- Insulation: Vinyl
- Terminal Body: Brass
- Plating: Tin



型号 ITEM NO.	插线规格 Name Tab	尺寸 DIMENSIONS					颜色 COLOR	说明 EXPLANATION
		W	L	d1	D	T		
FDFD 1.25-110(5)	0.5×2.8	3.8	19.0	1.7	3.7	0.35	红 RED	端头材质：黄铜 绝缘材质：PVC 导线截面：0.5-1.5mm ² 最大电流：IMAX=10A 最大耐温：75℃ Wire range：0.5-1.5mm ² A.W.G.:(22-16) Max.current=10A
FDFD 1.25-110(8)	0.8×2.8							
FDFD 1.25-187(5)	0.5×4.75							
FDFD 1.25-187(8)	0.8×4.75							
FDFD 1.25-205(5)	0.5×5.2							
FDFD 1.25-205(8)	0.8×5.2							
FDFD 1.25-250	0.8×6.35	7.5	21.5			0.4		
FDFD 2-110(5)	0.5×2.8	3.8	19.0	2.3	4.2	0.35	蓝 BLUE	端头材质：黄铜 绝缘材质：PVC 导线截面：1.5-2.5mm ² 最大电流：IMAX=15A 最大耐温：75℃ Wire range：1.5-2.5mm ² A.W.G.:(16-14) Max.current=15A
FDFD 2-110(8)	0.8×2.8							
FDFD 2-187(5)	0.5×4.75							
FDFD 2-187(8)	0.8×4.75							
FDFD 2-205(5)	0.5×5.2							
FDFD 2-205(8)	0.8×5.2							
FDFD 2-250	0.8×6.35	7.5	21.5			0.4		
FDFD 5.5-250	0.8×6.35	7.5	25.0	3.4	5.6	0.4	黄 YELLOW	端头材质：黄铜 绝缘材质：PVC 导线截面：4-6mm ² 最大电流：IMAX=24A 最大耐温：75℃ Wire range：4-6mm ² A.W.G.:(12-10) Max.current=24A