


FEMALE QUICK DISCONNECTS

母预绝缘接头



- Material
- Insulation: Vinyl
- Terminal Body: Brass
- Plating: Tin

型号 ITEM NO.	插线规格 Name Tab	尺寸 DIMENSIONS						颜色 COLOR	说明 EXPLANATION
		W	L	H	d1	D	T		
FDD 1.25-110(5)	0.5×2.8	3.8	19.0	10.0	1.7	3.7	0.3	红 RED	端头材质：黄铜 绝缘材质：PVC 导线截面：0.5-1.5mm ² 最大电流：IMAX=10A 最大耐温：75°C Wire range：0.5-1.5mm ² A.W.G.:(22-16) Max.current=10A
FDD 1.25-110(8)	0.8×2.8								
FDD 1.25-187(5)	0.5×4.75	5.8	19.0						
FDD 1.25-187(8)	0.8×4.75								
FDD 1.25-205(5)	0.5×5.2	6.5	19.0						
FDD 1.25-250	0.8×6.35	7.5	21.0						
FDD 1.25-312	0.8×8.0	9.1	24.0						
FDD 2-110(5)	0.5×2.8	3.8	19.0	10.3	2.3	4.3	0.35	蓝 BLUE	端头材质：黄铜 绝缘材质：PVC 导线截面：1.5-2.5mm ² 最大电流：IMAX=15A 最大耐温：75°C Wire range：1.5-2.5mm ² A.W.G.:(16-14) Max.current=15A
FDD 2-110(8)	0.8×2.8								
FDD 2-187(5)	0.5×4.75	5.8	19.0						
FDD 2-187(8)	0.8×4.75								
FDD 2-205(5)	0.5×5.2	6.5	19.0						
FDD 2-250	0.8×6.35	7.5	21.0						
FDD 2-312	0.8×8.0	9.1	24.0						
FDD 5.5-250	0.8×6.35	7.5	24.0	13.0	3.4	5.6	0.4	黄 YELLOW	端头材质：黄铜 绝缘材质：PVC 导线截面：4-6mm ² 最大电流：IMAX=24A 最大耐温：75°C Wire range：4-6mm ² A.W.G.:(12-10) Max.current=24A
FDD 5.5-312	0.8×8.0	9.1	26.5						
FDD 5.5-375	1.2×9.4	10.9	28.6						